

GreasePak GP-DMI-STD-2 Dosing Module Battery Operated

Capacity: 5 Litres. BBA Approved

View Product

Code : GP-DMI-STD-2



50% OFF Sale

£1,170.00

£584.99 / exc vat

£701.99 / inc vat

Add dosing fluid?

- Add 3x 5L boxes + £114.99 - No Thanks

Notes :

- Please check door entry sizes before ordering.
- Delivery is made to kerbside only.
- Drivers do not unpack or position goods.
- A 25% restocking charge will apply for all returned goods.

GreasePak is a CE certified biological drain maintenance system which releases a daily dose of bio-fluid into drains in order to degrade fats, oil, and grease (FOG) before they block your drains.

GreasePak complies with FOG removal laws such as BS EN1825, and benefits from a cost-effective and low maintenance refill procedure. The module is also classified under 'Hazard Group 1', meaning that the naturally-occurring microorganisms within its bio fluid are not harmful in any way.

Size

Unit	Height	Width	Depth
Mm	500	424	186
Cm	50	42.4	18.6
Inches (approx)	19	16	7

- Compact automatic dosing system
- Battery operated or mains powered models available
- Easy to install and operate with no water connection required
- Affordable, easy to manage and easy to clean with built in alarm to remind you to replace fluid
- Meets Building Regulations for an effective means of grease removal
- Use alone or in conjunction with a grease trap
- Most powerful, multi-strain, bio-fluid of its type - degrades FOGs into simple molecules that cannot reform or solidify
- Bio-fluid is 100% natural and safe
- Reduce the need for grease trap cleaning by over 50% - saving money!
- Reduce the chance of attracting vermin and pests
- Environmentally responsible
- GP-DMI-STD-2 499 mm 410m
- Dosing fluid sold seperately. (1x 5L box will last approx 1 month)