Lincat frifri



BM6 - Silverlink 600 Electric Counter-top Bain Marie - Dry Heat -Gastronorms - Base only -W 600 mm - 0.75 kW The Silverlink 600 Electric Dry Heat Bain Marie safely holds sauces, soups, gravy and precooked foods for up to two hours at the ideal serving temperature

SILVERLINK 600

- Dry heat bain marie
- Ideal for holding foods for up to 2 hours at serving temperature
- Base unit only supplied empty no gastronorms included

Power and Performance

- Plug and play for an easy installation
- Perfect for safely holding sauces, gravy & precooked foods
- Adjustable temperature control

Specifications

Summary	
---------	--


Range NameSilverlink 800Gastronorm Capacity6 x GN1/4Power TypeElectricTotal Power KW0.75Unit TypeCounter-topIP RatingIP33Available in UK OnlyNoTemperature ControlMechanicalUK Warranty2 Years Parts and Labour WarrantyHeight Counter your local dealerHeight Counter your local dealerGTIN Code5056105100461Soferiositositositositositositositositositosi				
Unit Type Available in UK OnlyCounter-top NoIP Rating Temperature ControlIP33We warranty Export Warranty Export Warranty Contact your local dealer 6050105100481Years Parts and Labour Warranty Contact your local dealer 6050105100481MechanicalKey SpecificationsWeights and DimensionsSecondary Secondary Unit Weight (External) mm Unit Width (External) mm Unit Weight Kg290Por Type Type of HeatGastronorm DryUnit Height (External) mm Unit Weight Kg290Supply ConnectionsShipping800Requires Installation No VK 3 Pin PlugNo YesPacked Weight Kg12.4Requires Installation No NG Ne Ne SecondaryPacked Weight Kg17Requires Installation Requires Installation No <b< th=""><th>Range Name</th><th>Silverlink 600</th><th>Gastronorm Capacity</th><th>6 × GN1/4</th></b<>	Range Name	Silverlink 600	Gastronorm Capacity	6 × GN1/4
Available in UK Only UK Warranty Export Warranty Entro Contact your local dealer GTIN CodeNo 2 Years Parts and Labour Warranty Contact your local dealer 5056105100461Temperature ControlMechanicalKey SpecificationsWeights and Dimensions290Pot Type Type of HeatGastronormUnit Height (External) mm Unit Width (External) mm Net Weight Kg290Supply ConnectionsShipping290Requires Installation Requires InstallationNo YesPacked Weight Kg17Requires Installation K S Pin PlugNo YesPacked Height cm Packed Depth cm70Requires Hardwiring Electrical Supply Rating Watts Single Phase AmpsNo Single Phase AmpsPacked Depth cm Single Phase Amps750	Power Type	Electric	Total Power kW	0.75
UK Warranty Export Warranty GTIN Code2 Years Parts and Labour Warranty Contact your local dealer 506105100481Key SpecificationsWeights and DimensionsFot Type Type of HeatGastronorm DryUnit Height (External) mm Unit Width (External) mm 00 Unit Depth (External) mm 12.4290Supply ConnectionsShippingRequires Installation Requires Installation No VG 3 Pin PlugNo Yes Yes Yes No Net Weight Kg70 Packed Height cmRequires Hardwiring Electrical Supply Rating Watts Single Phase AmpsNo So Single Phase Amps700 Single Phase Amps	Unit Type	Counter-top	IP Rating	IP33
Export Warnanty GTIN CodeContract your local dealer 5056105100461Key SpecificationsWeights and DimensionsPot Type Type of HeatGastronorm DryUnit Height (External) mm Unit Width (External) mm 00290Type of HeatOryUnit Height (External) mm Unit Weight Kg290Supply ConnectionsShipping600Requires Installation Requires Installation NoNoPacked Weight Kg17Requires Installation K 3 Pin PlugYesPacked Height cm49.5UK 3 Pin Plug Requires Hardwiring Electrical Supply Rating Watts 3.3YooPacked Depth cm70	Available in UK Only	No	Temperature Control	Mechanical
GTIN Code5058105100461Key SpecificationsWeights and DimensionsPot Type Type of HeatGastronorm DryUnit Height (External) mm Unit Width (External) mm 00 Unit Depth (External) mm 800 Net Weight Kg290Supply ConnectionsShipping12.4Requires Installation Requires Electrical Supply V S Packed Height cm17Requires Installation Requires Hardwiring Electrical Supply Rating Watts Single Phase AmpsNo So Packed Depth cm17Between State AmpsSo So	UK Warranty	2 Years Parts and Labour Warranty		
Key Specifications Weights and Dimensions Pot Type Gastronorm Unit Height (External) mm 290 Type of Heat Dry Unit Width (External) mm 600 Unit Depth (External) mm 600 600 No Net Weight Kg 12.4 Supply Connections Shipping Requires Installation No Packed Weight Kg 17 Requires Electrical Supply Yes Packed Height cm 49.5 UK 3 Pin Plug Yes Packed Depth cm 70 Requires Hardwiring No Packed Depth cm 70 Electrical Supply Rating Watts 750 J.3 J.3	Export Warranty	Contact your local dealer		
Pot Type Type of HeatGastronorm DryUnit Height (External) mm Unit Width (External) mm 600 Unit Depth (External) mm 600 Net Weight Kg290 600 600 12.4Supply ConnectionsShippingRequires Installation Requires Electrical SupplyNo YesPacked Weight Kg17 49.5Wit 3 Pin Plug Requires Hardwiring Electrical Supply Rating Watts Single Phase AmpsNoPacked Depth cm70 70	GTIN Code	5056105100461		
Type of HeatDryUnit Width (External) mm600Width (External) mm600NoWeight KgSupply ConnectionsShippingRequires InstallationNoPacked Weight KgRequires InstallationNoPacked Weight KgVK 3 Pin PlugYesPacked Height cmVK 3 Pin PlugYesPacked Width cmRequires HardwiringNoPacked Depth cmElectrical Supply Rating Watts750Single Phase Amps3.3	Key Specifications		Weights and Dimensions	
Unit Depth (External) mm Net Weight Kg600 600 12.4Supply ConnectionsShippingRequires InstallationNoPacked Weight Kg17Requires Electrical SupplyYesPacked Height cm49.5UK 3 Pin PlugYesPacked Width cm70Requires HardwiringNoPacked Depth cm70Electrical Supply Rating Watts750750Single Phase Amps3.3750	Pot Type	Gastronorm	Unit Height (External) mm	290
Net Weight Kg12.4Supply ConnectionsShippingRequires InstallationNoPacked Weight Kg17Requires Electrical SupplyYesPacked Height cm49.5UK 3 Pin PlugYesPacked Width cm70Requires HardwiringNoPacked Depth cm70Electrical Supply Rating Watts750YesPacked Depth cmSingle Phase Amps3.3YesYes	Type of Heat	Dry	Unit Width (External) mm	600
Supply Connections Shipping Requires Installation No Packed Weight Kg 17 Requires Electrical Supply Yes Packed Height cm 49.5 UK 3 Pin Plug Yes Packed Width cm 70 Requires Hardwiring No Packed Depth cm 70 Electrical Supply Rating Watts 750 Yes Yes Single Phase Amps 3.3 Yes Yes			Unit Depth (External) mm	600
Requires InstallationNoPacked Weight Kg17Requires Electrical SupplyYesPacked Height cm49.5UK 3 Pin PlugYesPacked Width cm70Requires HardwiringNoPacked Depth cm70Electrical Supply Rating Watts750750Single Phase Amps3.3750			Net Weight Kg	12.4
Requires Electrical SupplyYesPacked Height cm49.5UK 3 Pin PlugYesPacked Width cm70Requires HardwiringNoPacked Depth cm70Electrical Supply Rating Watts750	Supply Connections		Shipping	
UK 3 Pin PlugYesPacked Width cm70Requires HardwiringNoPacked Depth cm70Electrical Supply Rating Watts75073Single Phase Amps3.3750750	Requires Installation	No	Packed Weight Kg	17
Requires Hardwiring No Packed Depth cm 70 Electrical Supply Rating Watts 750 73 Single Phase Amps 3.3	Requires Electrical Supply	Yes	Packed Height cm	49.5
Electrical Supply Rating Watts 750 Single Phase Amps 3.3	UK 3 Pin Plug	Yes	Packed Width cm	70
Single Phase Amps 3.3	Requires Hardwiring	No	Packed Depth cm	70
	Electrical Supply Rating Watts	750		
Single Phase Voltage 230	Single Phase Amps	3.3		
	Single Phase Voltage	230		


Available Accessories	
CC6	Silverlink 600 Free-standing Ambient Open-Top Pedestal with Doors - W 600 mm
CN6	Silverlink 600 Free-standing Ambient Open-Top Pedestal without Doors - W 600 mm
HC6	Silverlink 600 Free-standing Heated Open-Top Pedestal with Doors - W 600 mm - 0.5 kW
HCL6	Silverlink 600 Free-standing Heated Pedestal with Legs and Doors - W 600 mm - 0.5 kW
SLS6	Silverlink 600 Free-standing Floor Stand - for units W 600 mm


Technical Picture











Lincat frifri

Lincat Limited

Whisby Road, Lincoln, LN6 30Z,

United Kingdom

Company No: 2175448

A member company of



Customer Care

Tel: +44 1522 875500

Email: care@lincat.co.uk

Export Customers

Tel: +44 1522 503250 Email: export@lincat.co.uk

Opening Hours

Monday – Friday: 8.30am – 5pm