

British Manufacturing since 1957



The Professionals Choice

WM7

Wall Mounted SureFlow Premium Water Boiler



FULL SPECIFICATION



WM7 Wall Mounted SureFlow Premium Auto Fill Water Boiler

| Туре | Premium Wall Mount – Wall mount Water Boiler |
|--|---|
| Country of Design & Manufacture | UK |
| CAPACITY, WEIGHTS & DIMENSIONS: | |
| Capacity (Litres) | 7 |
| Unit dimensions (W x D x H) mm | 350 x 220 x 498 |
| Packed dimensions (W x D x H) mm | 590 x 440 x 700 |
| Tap protrusion mm | 90mm |
| Product weight - empty (kg) | 8.4 |
| Product weight – full (kg) | 18.6 |
| Packed weight (kg) | 12.4 |
| CONSTRUCTION: | |
| Outer fabrication (body) construction | White Plastic FRABS |
| Tank construction | 304 & 316 grade Stainless Steel |
| Tank wall thickness | 0.9mm |
| ELECTRICAL: | |
| Power rating (kW) | 3 |
| Voltage supply | 230 V (50-60Hz) |
| Electrical supply | Single-phase, N & E (min break rating of 13amp required) |
| Electrical Connection | Wire into double-pole fused spare (minimum cable size: |
| | 1.5mm ²). Use of an ELCB is recommended |
| PLUMBING: | |
| Water inlet connection: | 3/4" BSP or 15mm push-fit |
| Mains water pressure range | 2 – 7 bar (28psi – 100psi) |
| Overflow/waste connection: | 15mm push-fit (extend if required: pipework to have a |
| | continuous fall (no longer than 500mm), no more than 3 |
| | right-angle bends. |
| PERFORMANCE: | |
| Water temperature delivered | 96°C (default) – can be adjusted if required |
| Heat up time to working temperature | 20 mins (full tank capacity) |
| Output per hour (@ default temperature setting) | 28 Litres (higher output/hour if set @ lower temperature) |
| Rapid draw-off | 7 Litres |
| Recovery per minute | 0.5 Litres |
| Stand-by power loss (idle mode) | 0.1 kW/h |
| FILTRATION: | |
| Multi-Filter (taste & odour, sediment & reduces lime-scale) | No (available as an optional extra if required) |
| OTHER FEATURES: | |
| 7 day programmable timer | Yes |
| Energy-saving ECO mode | Yes |
| Tank-baffle plates – unique design aids heat recovery & | Yes |
| reduces steam emissions to atmosphere | |
| Early warning lime-scale diagnostics (via LCD display) | Yes |
| Dual safety protection | Yes - Over-boil & boil-dry protection |
| STANDARDS & APPROVALS: | |
| WRAS approved | Yes |
| EMC Tested and Certified (EN 55014 & EN 61000) | Yes |
| Electrical Safety Tested and Certified to BS standard EN 60335-1 & 2 | Yes |
| WARRANTY & AFTER-SALES: | |
| Guarantee | 2 Year parts & labour |
| Spare parts, filters & accessories | Same day despatch (if ordered before 3pm) |
| | 23 (2. 22. 23 201010 Opini) |

Instanta Limited T: 01704 501114 F: 01704 501115 E: sales@instanta.com



