

Service Cabinets

General Purpose, Meat temperature

KICPR60LT



**430
STAINLESS
STEEL**



PV/PVX - suitable for fresh meat storage



Save Control System

Fitted with electronic controller that optimises power consumption and maximises energy saving



KICPRX40LT



FEATURES

White laminated exterior or AISI 430 stainless steel with anti fingerprint treatment

ABS interior with anti-bacterial treatment

5 adjustable shelves as standard

Replaceable gaskets

Reversible door

Lock as standard

2 adjustable front feet

TECHNICAL SPECIFICATIONS

	PR / PRX	PV / PVX
Controller:	Digital controller with temperature display	
Cooling:	Fan assisted	Ventilated
Defrost:	Automatic	Automatic
Refrigerant:	R134a	R134a
Climate Class	4	4
Temperature Range:	+2°C ~ +10°C	-2°C ~ +10°C
Power Supply:	13amp	

MODEL	FINISH	GROSS CAPACITY	EXT. DIMENSIONS (H x W x D mm)	ENERGY RATING	POWER CONSUMPTION	KWH /ANNUM	WEIGHT (kg)	RRP
KICPR40LT	White	380L	1872 x 600 x 620	G	160W	1219	78	£1,034.00
KICPR60LT		640L	1872 x 775 x 740	E	310W	1167	100	£1,194.00
KICPRX40LT	Stainless Steel	380L	1872 x 600 x 620	G	160W	1219	78	£1,121.00
KICPRX60LT		640L	1872 x 775 x 740	E	310W	1167	100	£1,329.00
KICPV40MLT	White	380L	1872 x 600 x 620	G	160W	1152	86	£1,162.00
KICPV60MLT		640L	1872 x 775 x 740	G	240W	1544	103	£1,420.00
KICPVX40MLT	Stainless Steel	380L	1872 x 600 x 620	G	160W	1152	86	£1,278.00
KICPVX60MLT		640L	1872 x 775 x 740	G	240W	1544	103	£1,534.00



OPTIONAL EXTRAS

Vaporiser kit fitted prior to despatch £161.00

