





EB3FX - FilterFlow Counter-top Automatic Water Boiler - W 250 mm - 3.0 kW Efficient both in its use of space and in its use of energy, the high-powered FilterFlow Automatic Water Boiler is perfect for busy staff rooms and anywhere where employees have to wait for the kettle to boil.

- Narrow 250mm footprint saves valuable counter space without compromising capacity or performance
- Built-in water filtration system improves water quality and reduces scale build-up. High volume, easy change FilterFlow cartridge
- Easily operated from a large, colour touchscreen display. Menu navigation is quick and easy with the temperature and timer simple to adjust
- Eco setting reduces the volume of boiling water by 50% for quieter periods. The intelligent predictive eco setting learns usage patterns and switches between eco mode and standard mode to deliver the required hot water output in the most economical way
- 7-day timer allows the boiler to be programmed to switch off overnight or at weekends to conserve energy
- Enhanced diagnostics identify possible causes. The on screen diagnostic information will enable the engineer to identify the parts needed and repair your water boiler at first visit

Specifications Power and Performance Summary **Hot and Cold Water Output** Range Name FilterFlow No Rapid Draw Off Litres **Power Type** Electric 11.0 **Unit Type** Counter-top Total Power kW 3.0 Available in UK Only Temperature Range °C 70 - 98 IP Rating **UK Warranty** 2 Years Parts and Labour Warranty IP23 **Export Warranty** Rapid Draw Off Cups Contact your local dealer 55 **GTIN Code Hourly Output Litres** 5056105101376 31 **Hourly Output Cups** 155 **Temperature Control** Electronic **Key Specifications Weights and Dimensions** Capacity Litres 15 N Unit Height (External) mm 596 Unit Width (External) mm Outlet Single-tap 250 Dispense Lock No Unit Depth (External) mm **WRAS Approved** Net Weight Kg 13.4 Yes **Supply Connections Shipping** Requires Installation Packed Weight Kg 16 Νn UK 3 Pin Plug Packed Height cm Yes 53 Packed Width cm **Requires Hardwiring** 69.5 No **Electrical Supply Rating Watts** Packed Depth cm 3,000 36.6 Single Phase Amps 13.0 Single Phase Voltage 230 Water Connection BSPT 3/4" Water Connection Pressure Bar 6.0

Available Accessories

BR55 EB3FX AND EB4FX WALL BRACKET
DP10 DESCALER POWDER










EBFX WATER FILTER - FROM 2015

Technical Picture













Lincat Limited

Whisby Road,

Lincoln, LN6 3QZ,

United Kingdom

Company No: 2175448

A member company of

Customer Care

Tel: +44 1522 875500

Email: care@lincat.co.uk

Export Customers

Tel: +44 1522 503250

Email: export@lincat.co.uk

Opening Hours

Monday - Friday:

8.30am - 5pm