Flexi-Deck Flexible PVC floor tiles ideal for wet areas

- Flexible PVC interlinking tiles ideal for industrial use.
- Holes allow drainage of liquid and debris.
- Specially designed underside studs have exceptional water . drainage properties.
- Anti-slip top surface for a safe footing in wet conditions. .
- Easily cleaned, rolled up and moved. .
- . Resistant to most oils and chemicals.
- Not just for use on floors. Can also be used on bar shelves as illustrated.

Colour Options

Grey

Red

- Hygienic PVC does not support the growth of bacteria. Holes provide efficient drainage and allow air to circulate. .
- .
- . Easily cleaned in a commercial dishwasher.





Technical Specification

Green

Blue

Material:	100% PVC
Product Height:	13mm
Operating Temperature:	-20°C to +95°C
Resistant to Chemicals:	PVC is resistant to many different chemicals, alkalis and general industrial chemicals. PVC resists alcohols, aliphatic hydrocarbons, oils, weak acids, strong mineral acids and alkalis. PVC resists oil and grease if properly cleaned. PVC does not resist organic solvents, ketones, esters and aromatic hydrocarbons. Please contact us for more specific details
Typical Applications:	Suitable for floors in work rooms and work areas where there is an increased risk of slipping. Can also be used on shelving
Installation Method:	Individual components that lock together to cover any desired length
Accessories:	Edges and Corners
Product Performance:	DIN 51130: 1992
Flame Retardancy:	Material pass UL 94 VO test
Country of Origin:	China

Sizes	Black	Blue	Red	Weight
Tile 30cm x 30cm (Pack of 9)	FD010001	FD020001	FD030001	3.80 kg
Female Edge (pack of 3)	FD010002F3	FD020002F3	FD030002F3	0.23 kg
Male Edge (pack of 3)	FD010002M3	FD020002M3	FD030002M3	0.23 kg
Corner (Pack of 4)	FD010004	FD020004	FD030004	0.06 kg
Sizes				
31265		Green	Grey	Weight
Tile 30cm x 30cm (Pack of 9)		FD040001	Grey FD060001	Weight 3.80 kg
			-	
Tile 30cm x 30cm (Pack of 9)		FD040001 FD040002F3	FD060001	3.80 kg