

SILVERLINK 600



GS7 - Silverlink 600 Electric Counter-top Griddle - Steel Plate - W 750 mm - 6.0 kW Whether you're cooking eggs, bacon, burgers or vegetables, the versatile Silverlink 600 Electric Griddle won't let you down.

- Two separately controlled heat zones give you the option of operating either zone independently to provide a smaller cooking area during quiet periods as well as offering versatility when cooking two separate meals simultaneously
- 12 mm thick machined steel plate providing even heat distribution and an easy to clean surface
- The plate is fully welded into the frame to prevent leaks and places where food and carbon can build up
- 2 cooking zone to give maximum flexibility during service
- Thermostatically controlled to give accurate temperatures during the cooking process for consistent results
- Front mounted control for easy of use during cooking

| Specifications | | | | | |
|--------------------------|-----------------------------------|---------------------------------|------------|--|--|
| Summary | | Power and Performance | | | |
| Range Name | Silverlink 600 | Total Power kW | 6.0 | | |
| Power Type | Electric | Temperature Range °C | 50-250 | | |
| Unit Type | Counter-top | IP Rating | IP33 | | |
| Available in UK Only | No | Cooking Area (Width x Depth) mm | 712 × 405 | | |
| UK Warranty | 2 Years Parts and Labour Warranty | Temperature Control | Mechanical | | |
| Export Warranty | Contact your local dealer | | | | |
| GTIN Code | 5056105104896 | | | | |
| Key Specifications | | Weights and Dimensions | | | |
| Number of Heat Zones | 2 | Unit Height (External) mm | 330 | | |
| Grill Plate Surface Type | Smooth | Unit Width (External) mm | 750 | | |
| Grill Plate Material | Steel | Unit Depth (External) mm | 620 | | |

| Grill Plate Material | Steel | Unit Depth (External) mm | 620 | |
|--------------------------------|----------------------------|--------------------------|------|--|
| | | Net Weight Kg | 48.9 | |
| Supply Connections | | Shipping | | |
| Requires Installation | Yes | Packed Weight Kg | 68.6 | |
| Requires Electrical Supply | Yes | Packed Height cm | 63.5 | |
| UK 3 Pin Plug | No | Packed Width cm | 85.5 | |
| Requires Hardwiring | Yes | Packed Depth cm | 70 | |
| Electrical Supply Rating Watts | 6,000 | | | |
| Single Phase Amps | 26.1 | | | |
| Single Phase Voltage | 230 | | | |
| Three Phase Amps | L1=13.0 ; L2=13.0 ; L3=N/A | | | |
| Three Phase Voltage | 400 | | | |


| Available Acce | essories |
|----------------|---|
| CC7 | Silverlink 600 Free-standing Ambient Open-Top Pedestal with Doors - W 750 mm |
| CN7 | Silverlink 600 Free-standing Ambient Open-Top Pedestal without Doors - W 750 mm |
| НС7 | Silverlink 600 Free-standing Heated Open-Top Pedestal with Doors - W 750 mm - 0.5 kW |
| HCL7 | Silverlink 600 Free-standing Heated Pedestal with Legs and Doors - W 750 mm - 0.75 kW |
| SB7 | 750 GRIDDLE SPLASHB |
| SLS7 | Silverlink 600 Free-standing Floor Stand - for units W 750 mm |


Product Code: GS7 Page Number: 1 Print Date: 15/03/2019




SILVERLINK 600

Technical Picture









Lincat Limited

Whisby Road,

Lincoln, LN6 3QZ,

United Kingdom

Company No: 2175448

A member company of

Customer Care

Tel: +44 1522 875500

Email: care@lincat.co.uk

Export Customers

Tel: +44 1522 503250

Email: export@lincat.co.uk

Opening Hours

Monday - Friday:

8.30am - 5pm