

PANTHER



P8B6PT - Panther 800 Series Free-standing Hot Cupboard - Bain Marie Top - 6GN - W 2180 mm -5.2 kW Helping to cater in demanding environments such as cafeterias, canteens and restaurants, the Panther 800 Series Hot Cupboard / Bain Marie is an effective way of holding food at the desired temperature, and is perfect for holding carvery and breakfast items either for self service or for back service.

- Helping to cater in demanding environments such as cafeterias, canteens and restaurants
- Pass through model with removable sliding doors to both sides provide enhanced workflow efficiency
- Fan assisted hot cupboard provides even heat distribution, fast heat up and recovery times, and lower energy usage. Four shelf positions allow adjustment to meet individual needs.
- Fully 1/1 GN compatible hot cupboard for operational efficiency. Units available to take 6 x 1/1 GN containers up to 150mm deep.
- Thermostatically controlled bain marie top can be operated with wet or dry heat. Accurate digital electronic control of the hot cupboard temperature, adjustable between 20 and 99 °C, ensures compliance with food hygiene regulations
- Double skinned construction provides efficient heat retention and a cool to touch exterior - safe and energy efficient. Removable doors and shelves allow access to the fully stainless steel interior for easy cleaning
- Supplied with two heavy duty multi-section chrome plated rod shelves capable of taking the heaviest loads
- Drain tap located inside the hot cupboard allows fast and easy draining

Specifications

- CPOSITIONIS						
Summary		Power and Performance				
Range Name	Panther	Gastronorm Capacity	6 × GN1/1			
Power Type	Electric	Total Power kW	5.2			
Unit Type	Free-standing	Temperature Range °C	20 - 99			
Available in UK Only	No	IP Rating	IP24			
UK Warranty	2 Years Parts and Labour Warranty	Plate Capacity	556			
Export Warranty	Contact your local dealer	Temperature Control	Top: Mechanical/Bottom: Electronic			
GTIN Code	5056105103547					

Key Specifications		Weights and Dimensions	
Drain Location	Right side interior mounted	Unit Height (External) mm	912
Number of Shelves included	2	Unit Width (External) mm	2180
Number of Shelf Positions	4	Unit Depth (External) mm	850
Pot Type	Gastronorm	Height (Internal) mm	432
Type of Heat	Wet/Dry	Width (Internal) mm	1995
Heated Base	Yes	Depth (Internal) mm	512
Heated Gantry	No	Shelf Dimensions Width mm	1929
Static or Mobile	Mobile	Shelf Dimensions Depth mm	512
		Net Weight Kg	167





Supply Connections		Shipping		
Requires Installation	Yes	Packed Weight Kg	197	
Requires Electrical Supply	Yes	Packed Height cm	110	
UK 3 Pin Plug	No	Packed Width cm	222	
Requires Hardwiring	Yes	Packed Depth cm	90	
Electrical Supply Rating Watts	5,200			
Single Phase Amps	22.6			
Single Phase Voltage	230			

Available Options

Overshelf or Gantry

PS6A1 - 1 Ambient Overshelf
PS6A2 - 2 Ambient Overshelves
PS6A3 - 3 Ambient Overshelves
PS6H1 - 1 Heated Overshelf
PS6H2 - 2 Heated Overshelves
PS6H3 - 3 Heated Overshelves

Door Locks

PDL6 - Lockable Door

Corner Guards

PCG - Corner Guards [Set of Four]

Legs/Castors

PGK1

PGK4

PLK - Legs [non chargeable]

Available Accessories

CP16 - CARVERY PAD [1/1 GASTRONORM SIZE]

PGK1 - GASTRONORM PACK

PGK4 - GASTRONORM PACK

PGK19 PGK19 - GASTRONORM PACK PGK2 PGK2 - GASTRONORM PACK PGK20 PGK20 - GASTRONORM PACK PGK21 PGK21 - GASTRONORM PACK PGK22 PGK22 - GASTRONORM PACK PGK23 PGK23 - GASTRONORM PACK PGK24 PGK24 - GASTRONORM PACK PGK25 PGK25 - GASTRONORM PACK PGK3 PGK3 - GASTRONORM PACK

 PGK7
 PGK7 - GASTRONORM PACK

 PHTC
 PHTC - CERAMIC INSERT [1/1 GASTRONORM SIZE]

 PHTG
 PHTG - GLASS INSERT [1/1 GASTRONORM SIZE]


PLK/S PLK/S - LEG KIT[FOR CONVERSION IN THE FIELD]


Technical Picture


Product Code: P8B6PT Page Number: 2 Print Date: 15/03/2019













Lincat Limited

Whisby Road,

Lincoln, LN6 3QZ,

United Kingdom

Company No: 2175448

A member company of

Customer Care

Tel: +44 1522 875500

Email: care@lincat.co.uk

Export Customers

Tel: +44 1522 503250

Email: export@lincat.co.uk

Opening Hours

Monday - Friday:

8.30am - 5pm